

Dual-band, Ceiling Mount MIMO Omnidirectional Antennas

The PCTCMI2458-6 and PCTCMI2458-3 dual-band MIMO antennas provide diversity coverage of 2.4-2.5 GHz WiFi, 4.9-5.9 GHz Public Safety/ISM/WiFi/WiMAX broadband wireless frequencies in an attractive, low profile housing. These antennas are designed for in-building ceiling mount installations utilizing 802.11n multi-band wireless LAN access point radios. Two easy to install models are available for use with 6-port or 3-port MIMO radios.

Features

- Multi-band coverage of 2.4-2.5 GHz ISM, 4.9-5.9 GHz broadband wireless frequencies with every element
- Six-port or three-port dual band integrated elements terminated with high performance, low loss Plenum rated cable
- Single (PCTCMI2458-3) or dual (PCTCMI2458-6) stud mount cable exits for quick and simple installation
- Attractive low profile radome addresses in-building aesthetic considerations
- UL 94-V0 listed materials and Plenum rated cable for compliance to strict building safety code specifications



PCTCMI2458-6 (dual stud cable exit) PCTCMI2458-3 (single stud cable exit)

RF/Electrical Specifications

Model	Frequency Range	Vertical Beamwidth	Nominal Gain	VSWR
PCTCMI2458-6	2.4-2.5 GHz	55°	2.5 dBi (2.4-2.5 GHz)	< 2.0:1
	4.9-5.9 GHz	45°	3.0 dBi (4.9-5.9 GHz)	
PCTCMI2458-3	2.4-2.5 GHz	55°	2.5 dBi (2.4-2.5 GHz)	< 2.0:1
	4.9-5.9 GHz	45°	3.0 dBi (4.9-5.9 GHz)	

Mechanical Specifications

Model	Dimensions	Temperature Range	Cable
PCTCMI2458-6	9.1 L x 6.6 W x 1.6 D inches	-30° C to +70° C	Six (6) 3-foot Plenum RG-58/U CL2P
PCTCMI2458-3	9.1 L x 6.6 W x 1.6 D inches	-30° C to +70° C	Three (3) 3-foot Plenum RG-58/U CL2P



Technical Data

Maximum Power: 25 watts
Nominal Impedance: 50 ohm
Polarization: Vertical, linear
Antenna Housing Material: Off-white PC/ABS Plastic
Connectors: Reverse Polarity SMA Male*
Mounting Method: Ceiling Mount. Single 1.5-inch stud mount cable exit (PCTCMI2458-3) Two 1.5-inch stud mount cable exits (PCTCMI2458-6) 7/8-14 UNF plastic HEX-nuts and flat washers included

* Standard models. Contact Customer Service to request other connector options.